

HYBRID LINE

power
and innovation

**designed and created
for your needs**

9,5h run time

**remote
telemetry**



Designed to provide
an exceptional level
of performance
for every work on site
ensuring the right
balance between power
and ease of use

**MGTP
5000/12 TH**



**more sustainable
and environmentally
friendly future**

 **TRIME**[®]
Power Division

MGTP 5000/12 TH



REDUCTION
emissions **CO₂**

APPLICATIONS



Constructions



Road works



Films set



Events

FEATURES

- ✓ DSE 3110 controller
- ✓ 5" Touch monitoring display controller
- ✓ Communication-centre device
- ✓ 48V/400A BMS to protect the batteries
- ✓ 4G/GPS Antenna + Modem
- ✓ **Remote telemetry & management**
- ✓ Auto recharge of the batteries
- ✓ Automatic peak shaving mode
- ✓ Sides forklift pockets & Central lifting hook
- ✓ Lockable control panel
- ✓ Main circuit breaker & Earth leakage relay
- ✓ Emergency Stop button
- ✓ Bunded tank
- ✓ 3-way valve for external tank
- ✓ Battery switch

hybrid
technology



HYBRID LINE

Code	RP47-5MS11
Dimensions	
L x W x H (mm)	1700x1066x1450
Weight (Kg)	800
Technical Data	
Continuous power (VA)	5000
Battery pack capacity (Wh)	11776
Capacity available DOD 80% (Wh)	9421
Voltage (V)	230
Frequency (Hz)	50
Inverter	
Nominal power (VA)	5000
Q.ty	1
System voltage (V)	48
Max charging current (A)	70
Batteries	
Type	LiFeP04
Q.ty	2
Nominal Voltage (V)	25,6
Nominal Capacity (Ah)	230
Cycle Life DOD 80%	>4000
Engine	
Brand	Kubota
Model	D1105
Speed	1500
Cooling system	Water
Emission	Stage V
Fuel Tank (l)	200
Alternator	
Brand	Zanardi
Model	PE28 2VS/4
Rated output (kVA)	8
Frequency (Hz)	50
Power factor (cos φ)	0,8
Distribution panel	
Inlet Plug	1x 32A-230V
Outlet Sockets	1x 32A-230V
	1x 16A-230V
Performances	
Running time on batteries (h) 25% load	9,5
Running time on batteries (h) 50% load	4,5
Running time on batteries (h) 75% load	3,0
Recharge time from engine (h)	5
Available options	
MC4 connectors + MPPT solar charger for external solar panels	
Mat heating system for batteries to work in cold ambients	



easy handling & transportability



TRIME®

Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.