

**designed and created
for your needs**

Designed to provide
an exceptional level
of performance
for every work on site
ensuring the right
balance between power
and ease of use

PORTABLE LINE

DIESEL

**power
and innovation**

MGTP
4,5 Y DM AE

MGTP
6,5 Y DM AE

MGTP
7 Y DT AVR

MGTP
7 Y DT AE

MGTP
11 L DM AE

MGTP
11 L DT AE

MGTP
15 L DT AE



**more sustainable
and environmentally
friendly future**



TRIME
Power Division



ELECTRIC START
ENGINE
3000 r.p.m.



LWA
2000/14/CE



MGTP 4,5 Y DM AE



MGTP 6,5 Y DM AE



MGTP 7 Y DT AVR



MGTP 7 Y DT AE



Code	PP70-4M00	PP71-7M00	PP73-7T00	PP72-7T00
On board control panel equipped with:	- Hour counter - Volt meter - Main circuit breaker - 1x16A 1ph 230V EEC socket - 1x16A 1ph 230V Schucko socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 1ph 230V EEC socket - 1x16A 1ph 230V EEC socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 3ph 400V EEC socket - 1x16A 1ph 230V EEC socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 3ph 400V EEC socket - 1x16A 1ph 230V EEC socket
Generator				
Type	Linz E1C10S F	Linz E1C10M H	Linz E1S10MIKE	Linz E1S10M H
Power	4,5 kVA 230V	6,5 kVA 230V	7 kVA 400V	7 kVA 400V
Frequency	50 Hz	50 Hz	50 Hz	50 Hz
Engine				
Engine type	YANMAR L70 AE	YANMAR L100 AE	YANMAR L100 AE	YANMAR L100 AE
N° cylinders	1	1	1	1
Power	6,7 HP	10 HP	10 HP	10 HP
Engine speed	3000 r.p.m.	3000 r.p.m.	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air	Air	Air
Fuel	Diesel	Diesel	Diesel	Diesel
Starting system	Electric	Electric	Electric	Electric
Technical Data				
Fuel tank capacity	3,5 lt	6 l	5,4 l	5,4 l
Running Time	3,5 h	3,5h	3,5 h	3,5h
Dimensions				
Dimensions (LxWxH) mm	760 x 520 x 690	760 x 520 x 690	760 x 520 x 690	760 x 520 x 690
Weight (Kg)	100	120	122 Kg	122
Options	Trolley	Trolley	Trolley	Trolley





LOMBARDINI



ELECTRIC START
ENGINE
3000 r.p.m.



LWA
2000/14/CE



AIR
cooled

MGTP 11 L DM AE



MGTP 11 L DT AE



MGTP 15 L DT AE



Code	PP74-11M00	PP75-11T00	PP76-15T00
On board control panel equipped with:	- Hour counter - Volt meter - Main circuit breaker - 1x32A 1Ph 230V EEC socket - 1x16A 1ph 230V EEC socket	- Hour counter - Volt meter - Main circuit breaker - 1x16A 3ph 400V EEC socket - 1x16A 1ph 230V EEC socket	- Hour counter - Volt meter - Main circuit breaker - 1x32A 3ph 400V EEC socket - 1x16A 1ph 230V EEC socket
Generator			
Type	Linz E1C11M B	Linz E1S10L L	Linz E1S11M B
Power	11 kVA 230V	11 kVA 400V	15 kVA 400V
Frequency	50 Hz	50 Hz	50 Hz
Engine			
Engine type	LOMBARDINI 25LD330	LOMBARDINI 25LD330	LOMBARDINI 25LD425
N° cylinders	2	2	2
Power	16,3 HP	16,3 HP	16,3 HP
Engine speed	3000 r.p.m.	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air	Air
Fuel	Diesel	Diesel	Diesel
Starting system	Electric	Electric	Electric
Technical Data			
Fuel tank capacity	20 l	20 l	20 l
Running Time	7,7 h	7,7h	6,9 h
Dimensions			
Dimensions (LxWxH) mm	850 x 520 x 750	850 x 520 x 750	850 x 520 x 750
Weight (Kg)	145	145	160
Options	Trolley	Trolley	Trolley



easy handling & transportability



TRIME[®]

Sales Dept. +39 0382 406 252 - www.trime.it - info@trime.it

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.